2SC1384

Rev.E Mar.-2016

蓝箭电子 BLUE ROCKET ELECTRONICS

DATA SHEET

/ Descriptions

WR0<50P ṂṂÞ QSQ ÆṀчs ‖ ㄱ Silicon NPN transistor in a TO-92LM Plastic Package.

/ Features

ت ⊐ я ∪ Ӈ/лъ 5VD9;7 Ӣ ´ ˡ ệ 5Ќ6 ב ڑ.


Low $V_{CE(sat)}$,2 3W output in complementary pair with 2SA684.

/ Applications

ӂ ˍ ḽ ı ' ѽ ᶻ ⊐ ɨ ט

AF power amplifier and driver applications.

/ Equivalent Circuit



/ Pinning



PIN1 χ Base PIN 2 χ Collector PIN 3 χ Emitter


/ h_{FE} Classifications & Marking

h_{FE} Classifications Symbol	Q	R	S
h_{FE} Range	85~170	120~240	170~340

v ‴Ω Parameter	ϒ N Symbol	‴Ω Ë Rating	D Ч Unit
Collector to Base Voltage	V_{CBO}	60	V
Collector to Emitter Voltage	V_{CEO}	50	V
Emitter to Base Voltage	V_{EBO}	5.0	V
Collector Current - Continuous	I_C	1.0	A
Collector Current – Continuous(Pulse)	I_{CP}	1.5	A
Collector Power Dissipation	P_C	1.0	W
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}	-55 150	T'

/ Electrical Characteristic Curve

P_C — T_a




T_a (°C)

I_C — V_{CE}


V_{CE} (V)

I_C — I_B

I_B (mA)




C_{ob} — V_{CB}




V_{CB} (V)

/ Package Dimensions

TO-92LM Unit: mm



/ Marking Instructions




ب ″ χ	
EU=	₩ ३ И Ґ
F46 ; 7 χ	₩ ʒ N Ґ
T=	₩ k IH ‘ 6 Ґ
---- χ	₩ ł ғ ń N Ґ ı ₰ ł ғ ń N Ψ ק

Note:

BR:	Company Code.
C1384:	Product Type.
Q:	h_{FE} Classifications Symbol
****:	Lot No. Code,code change with Lot No.

( ) / Temperature Profile for Dip Soldering(Pb-Free)



ب ˝ χ

1 Ĺ ♬ □ ỷ 25 Ḱ 150 ɬ ı ˋH ڑ 60 Ḱ 90sec;

2 Š Ө □ ỷ 255 ° 5 ɬ ı ˋH ڑ ˋY ﾊ ㎛ 5 ° 0.5sec;

3 ì ˙ ϒ ˛ ɔ ෯ ỷ ㎛ 2 Ḱ 10 ɬ /sec.

Note:

1.Preheating:25~150 ɬ , Time:60~90sec.

2.Peak Temp.:255 ° 5 ɬ , Duration:5 ° 0.5sec.

3. Cooling Speed: 2~10 ɬ /sec.

/ Resistance to Soldering Heat Test Conditions

□ ỷ χ 270 ° 5 ɬ ˋH ڑ χ 10 ° 1 sec. Temp.:270 ° 5 ɬ Time:10 ° 1 sec

/ Packaging SPEC.

ˇQ ţ ϒ Ł / BULK

Package Type	Units					Dimension		(unit mm3)
	Units/Bag /	Bags/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Bag	Inner Box	Outer Box
TO-92LM	1,000	8	8,000	5				