/ Revised record

G	2018-5				
H	2019-2-22	2	t_{rr} 8 4		
A	2022-3-15	all	BR Q H Q, AEC-Q101 , H Q 245±5℃ 5± 0.5sec 255± 5℃ 5±0.5sec		

BR1N4148WQ

Rev.A Mar.-2022

DATA SHEET

/ Descriptions

SOD-123

Silicon Diode in a SOD-123 Plastic Package.

/ Features


AEC-Q101

Fast switching diodes, Qualified to AEC-Q101 Standards for High Reliability, HF Product.

/ Applications

Small signal diode, Meet the stringent requirements of automotive applications.

/ Equivalent Circuit



/ Pinning

1 **2**


PIN1:Cathode PIN2:Anode


/ Marking


Marking	QA2

参数 Parameter	符号 Symbol	数值 Rating	单位 Unit

/ Electrical Characteristic Curve







( ) / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

1	150 200 60 120sec;	1.Preheating:150~200 , Time:60~120sec.
2	255 5 5 0.5sec;	2.Peak Temp.:255 5 , Duration:5 0.5sec.
3	2 10 /sec.	3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260 5 10 1 sec. Temp.:260 5 Time:10 1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm^3)		
	只卷盘	卷盘盒	只盒	盒箱	只箱		盒	箱

〃