/ Descriptions

Low dropout linear regulator in a SOT23-3 Plastic Package.


/ Features

Low power consumption,Low voltage drop,Small temperature drift coefficient,High input voltage up to 24V,The static current 1.5 A,The output voltage accuracy ,HF Product.


/ Applications


For use in power equipment,Communication equipment,Audio and video equipment.

/ Equivalent Circuit



/ Pinning






1	GND		3	VIN	
2	VOUT				

/ Marking


See Marking Instructions.

/ Typical Application Circuit


/ Basic Application



/ High Output Current Voltage Regulator




/ Short-Circuit Protection




/ Typical Application Circuit


/ Circuit for Increasing Output Voltage



/ Constant Current Regulator




/ Package Dimensions



BRCO7533MMC

Rev C RM R a e - R 1 7 eS H E T

( ) / Temperature Profile for IR Reflow Soldering(Pb-Free)



		Note:
1	150 180 60 90sec;	1.Preheating:150~180 , Time:60~90sec.
2	245 5 5 0.5sec;	2.Peak Temp.:245 5 , Duration:5 0.5sec.
3	2 10 /sec.	3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260 5	10 1 sec.	Temp.:260±5	Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension		(unit mm³)
	Units/Reel /	Reels/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Reel	Inner Box	Outer Box
SOT23-3	3,000	10	30,000	4	120,000	7 ×8	210×205×205	445×435×230

/ Notices