20htpe ɦ be ₸ D2


t

Pa			
Drain-Source Voltage			
t	I_{DM}	100	A
e	V_{GS}	±20	V
		78	W

BRCS150N12SZC

Rev.A Jun.-2022

/ Marking Instructions



BR

150N12S

****

Note

BR	Company Code
150N12S	Product Type
****:	Lot No. Code, code change with Lot No

( ) / Temperature Profile for IR Reflow Soldering(Pb-Free)

				Note:
1	150	180	60 90sec;	1.Preheating:150~180℃, Time:60~90sec.
2	245±5		5±0.5sec;	2.Peak Temp.:245±5℃, Duration:5±0.5sec.
3		2	10℃/sec.	3. Cooling Speed: 2~10℃/sec.

/ Resistance to Soldering Heat Test Conditions

260±5℃	10±1 sec.	Temp.:260±5	Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units 包装数量					Dimension 包装尺寸 (unit: mm^3)		
	Units/Reel	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
PDFN5 × 6	5000	2	10000	6				