/ Descriptions

1.5A ABF
1.5A Surface Mount Glass Passivated Bridge Rectifier, ABF thin package.


/ Features

1000V 1.5A
Glass Passivated Chip Junction,Reverse Voltage: 1000V,Forward Current:1.5A, Fast reverse recovery time,Designed for Surface Mount Application.Halogen free product.

/ Applications

.
General purpose.


/ Equivalent Circuit



/ Pinning



PIN	DESCRIPTION
1	Input Pin (~)
2	Input Pin (~)
3	Output Anode (+)
4	Output Cathode (-)



/ Marking

See Marking Instructions.

/ Absolute Maximum Ratings(Ta=25)

Parameter	Symbol	Rating	Unit
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	1000	V
Maximum RMS Voltage	V_{RMS}	700	V
Maximum DC Blocking Voltage	V_{DC}	1000	V
Average Rectified Output Current at T_c = 125	I_o	1.5	A
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load	I_{FSM}	50	A
Typical Junction Capacitance Note1	C_j	35	pF
Typical Thermal Resistance Note2	R_{JA}	70	/W
Operating and Storage Temperature Range	T_j,T_{stg}	-55~150	

Note:


1.Measured at 1MHz and applied reverse voltage of 4 V D.C.

2. Mounted on glass epoxy PC board with 4 × 1.0" X 1.0" (2.54 X 2.54 cm) copper pad.


/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions	Rating	Unit
Forward Voltage per element	V_F	I_F=1.5A	1.3	V
Maximum DC Reverse Current at Maximum DC Blocking Voltage	I_R	T_a=25	5.0	A
		T_a=125	50	A
Maximum Reverse Recovery Time	t_{rr}	I_F =0.5A I_R=1.0A I_{rr}=0.25A	200	ns

/ Electrical Characteristic Curve




/ Package Dimensions




/ Marking Instructions

Marking

Type number	Marking code
FTB10F-15	F10F15



/ Marking Instructions



F10F15


******** 1 ***** 3 *****

Note:

F10F15 Product Type Code

******** Lot No. Code The 1st ***** means:YM Code The last 3 ***** means:little Lot No Code

( ) / Temperature Profile for IR Reflow Soldering(Pb-Free)



| | | |