/ Descriptions

TO-3P

Schottky Barrier Diode in a TO-3P Plastic Package.

/ Features


Low forward voltage drop, low power losses, High efficiency operation.

/ Applications


OR-ing DC-DC

For use in high frequency inverters, switching power supplies, freewheeling diodes, OR-ing diode, dc-to-dc converters and reverse battery protection.

/ Equivalent Circuit



/ Pinning



PIN1 Anode PIN 2 Cathode PIN 3 Anode


/ h_{FE} Classifications & Marking


See Marking Instructions.

Parameter	Symbol	Rating	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_{RWM} V_{DC}	100	V
RMS Reverse Voltage	V_{RMS}	70	V
Average forward current	$I_{F(AV)}$	2 × 20	A
Non-Repetitive Peak Forward Surge Current	I_{FSM}	300	A
Thermal Resistance Junction to Ambient case	$R_{\theta Jc}$	2.8	/W
Operating and Storage Temperature Range	T_j T_{stg}	-40 +150	


Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Reverse Breakdown Voltage	V_{BR}	I_R=1mA(Ta=25)	100			V
		I_F				
Forward Voltage	V_F					

/ Electrical Characteristic Curve






/ Package Dimensions



/ Marking Instructions



BR


LV40100PT

****

Note:

BR:	Company Code.
LV40100PT:	Product Type.
****:	Lot No. Code, code change with Lot No.

( ) / Temperature Profile for Dip Soldering(Pb-Free)



					Note:
1	25	150		60	90sec;
2	255±5				5±0.5sec;
3			2	10	/sec.

1.Preheating:25~150 , Time:60~90sec.
2.Peak Temp.:255±5 , Duration:5±0.5sec.
3. Cooling Speed: 2~10 /sec.

• ±