MBRJ10150CT

Rev.E Mar.-2016

蓝箭电子 BLUE ROCKET ELECTRONICS

DATA SHEET

/ Descriptions

TO-220S ĻĻĿ ⁄ ⁿ⁀ ‖ ㄱ Schottky diode in a TO-220S Plastic Package.

/ Features

ˈΩ ă Ḩ ı ѽ ' ≍


Low power loss, high efficiency.

/ Applications


ᵹ̂ ≍ ḛ Ḩ я ᶻ ɔ ㄴ̃Ω ㄴ‾ ‖ ㄱ ı ㅅ ㄴ‾ ‖ ㄱ

For high frequency, high voltage, high current rectifier diode, freewheeling diode.

/ Equivalent Circuit



/ Pinning



PIN1 χ Anode PIN 2 χ Cathode PIN 3 χ Anode PIN 4 χ NC

/ h_{FE} Classifications & Marking


ð м ヽ ب ˝ See Marking Instructions.


v ‴Ω Parameter	ϒ N Symbol	‴Ω Ö Rating	D Ч Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage Reverse Voltage	V_{RRM} V_{RWM} V_{RM}	150	V
RMS Reverse Voltage	$V_{R(RMS)}$	105	V
Average Rectified Forward Current	$I_{F(AV)}$	2*5	A
Non Repetitive Peak Surge Current	I_{FSM}	100	A
Thermal Resistance Junction to Case	$R_{\theta Jc}$	3.5	/W
Junction Temperature Range	$T_{j\ MAX}$	150	
Storage Temperature Range	T_{stg}	-65 150	


v ‴Ω Parameter	ϒ N Symbol	‖ ⁝ ˥ ţ Test Conditions	ѡ ņ Ö Min	Ɛ ʒ Ö Typ	ѡ ᶻ Ö Max	D Ч Unit
Reverse Voltage	$V_{(BR)R}$	I_R=0.3mA	150			V
Forward Voltage	V_F	I_F=5A T_j=25			0.85	V
		I_F=5A T_j=125			0.70	V

s

/ Electrical Characteristic Curve









/ Package Dimensions

TO-220S Unit: mm



Symbol	Dimensions In Millimeters Min.	Max.	Symbol	Dimensions In Millimeters Min.	Max.

/ Marking Instructions



͡ ˝ χ	
EU χ	ѭ ϗ ᴎ Γϧ
P EUM43483 χ	ѭ ϳ ᴺ Γϧ
FW=	ѭ ᴖ ᵚ ᒍ ⎯
---- χ	ѭ ᵻ ᶠ ᵑ̈ ᴺ Γϧ ᵻ ₺ ᵻ ᶠ ᵑ̈ ᴺ Ψ ᑭ
Note:	
BR:	Company Code
MBRJ10150 χ	Product Type.
CT:	Internal Structure
****:	Lot No. Code, code change with Lot No.