
TO-252 PNP Silicon PNP transistor in a TO-252 Plastic Package.

, , , MPSA42D

High voltage, low saturation voltage, low collector output capacitance, complementary pair with MPSA42D.

High voltage control circuit.





PIN1 Base PIN 2,4 Collector PIN 3 Emitter

/ h_{FE} Classifications & Marking


See Marking Instructions.

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	-300	V
Collector to Emitter Voltage	V_{CEO}	-300	V
Emitter to Base Voltage	V_{EBO}	-5.0	V
Collector Current - Continuous	I_C	-500	mA
Collector Power Dissipation	P_C	625	mW
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}	-55 150	

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector to Base Breakdown Voltage	[redacted]O	[redacted].00μA I_E=0	-300	[redacted]		V
Collector to Emitter Breakdown Voltage	V_{CEO}					


/ Electrical Characteristic Curve






/ Package Dimensions





/ Marking Instructions



BR


A92D

****

Note:

BR:	Company Code
A92D:	Product Type.
****:	Lot No. Code, code change with Lot No.

( ) / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

1